


## DWP-Series Deep Watering Panels

Incorporates 90° ribs with deep watering channels with aeration vents. Vents are located along the channel facing the root ball zone. The system is designed to use up to 30% less water by evenly distributing water and nutrients directly into the root ball zone and base of the barrier, while deflecting roots downward away from the hardscape. The DWP-Series can be used in both linear and Tree Well Application.

**Linear Application:** For root pruning of existing trees or in planting situations where one or more trees are in close proximity to hardscapes.

-OR-

**Tree Well Application:** For new tree planting or when the hardscape encircles the planter



### Features:

- Flexible Top Safety Edge
- Versatile barrier for water conservation used in linear or Tree Well Application.
- Manufactured with recycled plastic
- Raised 90° root deflecting ribs and vented deep watering channels for aeration and equal water distribution to root ball and barrier base
- 90° ½"-¾" raised rib, side interlocking, panel to panel joining system
- Adjustable anti-lift polyethylene panels which can be separated into 1' (30.5 cm) sections

### SPECIFICATIONS

**DWP-Series:** DWP12-2, DWP18-2, DWP24-2

90° ½"-¾" raised rib, side interlocking panel to panel joining system

**Material:** Polyethylene with ultraviolet inhibitors

**Thickness:** 0.085"


| MATERIAL                      | Polyethylene     |                              |
|-------------------------------|------------------|------------------------------|
| THICKNESS                     | 0.085"           |                              |
| PROPERTIES                    | ASTM TEST METHOD | VALUE POLYETHYLENE COPOLYMER |
| Tensile Stress @ Yield        | D638             | 4100 TO 4300 PSI             |
| Elongation @ Break            | D638             | 40%                          |
| Tensile Modulus of Elasticity | D638             | 150,000 PSI                  |
| Flexural Stiffness            | -                | -                            |
| Cantilever Beam               | D747             | 125,000 PSI                  |
| Tensile Impact                | D1822            | 50Ft. lbs/in <sup>2</sup>    |
| Environmental Stress          | -                | -                            |
| Crack Resistance              | D1693            | 1 Hr.                        |
| Hardness, Shore D             | D2240            | 68                           |

#### U.S. Standard


**For Technical or Field Support, please call: 714.632.7083**

Tolerances may vary in order to maintain the integrity of post-consumer materials, and assure the material structure. We make no other warranties, express or implied, and specifically disclaim the warranty of merchantability or fitness for a particular purpose.

### TREE WELL APPLICATION



### LINEAR APPLICATION



## DWP-SERIES Root Barrier Panels

The **Century DWP-Series Deep Watering Panels** are pre-assembled in 2' (61 cm) long segments. The segments can be combined to create various lengths of barrier. The vented water channels located on the inside of the panel are designed to provide water and aeration directly and evenly to the root zone.

### I. SPECIFICATIONS

- The root barrier shall be **DWP-Series** manufactured by Century Products, 1144 N Grove Street, Anaheim, CA 92806, (714) 632-7083, or approved equivalent.
- The barriers are black molded modular panels manufactured using 50% recycled polyethylene plastic with ultraviolet inhibitors and 0.085" (2.16 mm) in thickness. Each panel has vertical 90° root deflecting ribs and vented channels for deep watering and aeration, protruding 7/8" in height. The ribs have a minimum thickness of 0.085" (2.16 mm) and are placed 4 1/2" (11.4 cm) apart. An integrated 90° 1/2"-3/4" raised rib, panel to panel joining system for instant assembly by sliding one panel into another.

### II. INSTALLATION

- The specified number of panels shall be joined together and placed along the hardscapes creating a linear planting application or connected to outline the tree well/planter.
- Root deflecting ribs and water aeration channels are always installed facing the root ball.
- Always install panels 1"-2" above grade to avoid root penetration above the barrier.
- Prepare your installation for specified application as depicted in illustrations. (Assemble barrier as shown in figure 1)
- Recommended for linear or tree well applications. Back fill with existing native soil. If necessary for drainage, use gravel or crushed rock. Avoid backfill less than 3/4" or greater than 1 1/2". Finish to grade. Do not distort barrier during installation.
- Technical Questions? Call Century Products at 714. 632.7083 for assistance.

**Fig. 1**

